

MODEL- 4LB/6LB/9LB/12LB

DUAL FACE LAPPING & POLISHING MACHINES



規格 型式	4LB	6LB	9LB	12LB	MODEL SPECIFICATIONS
研磨盤直徑	265 ϕ ×114 ϕ ×16T	374 ϕ ×150 ϕ ×20T	630 ϕ ×245 ϕ ×30T	763 ϕ ×270 ϕ ×40T	DIAMETER OF LAPPING PLATE
最大加工直徑	70 ϕ	110 ϕ	180 ϕ	220 ϕ	MAXIMUM DIAMETER OF PRODUCTS
夾具直徑	99.6 ϕ (PCD)	139.3 ϕ (PCD)	228.5 ϕ (PCD)	283.6 ϕ (PCD)	DIAMETER OF CARRIER(PCD)
夾具數量	5枚	5枚	5枚	5枚	NUMBER OF CARRIERS
最小厚度	30 μ	80 μ	300 μ	300 μ	MINIMUM THICKNESS OF PRODUCTS
下盤轉速	0~60RPM	0~60RPM	0~60RPM	0~60RPM	ROTATING SPEED OF LOWER LAPPING PLATE(R.P.M.)
反轉機構	CW & CCW	CW & CCW	CW & CCW	CW & CCW	REVERSAL MECHANISM OF CARRER
研磨主馬力	0.75KW	1.5KW	3.7KW	5.5KW	MAIN MOTOR OF LAPPING
拋光主馬力	1.5KW	2.2KW	5.5KW	7.5KW	MAIN MOTOR OF POLISHING
尺寸	830×600×1700	930×700×1930	1480×880×2400	1610×1200×2400	MACHINE DIMENSIONS
重量	600KGS	800KGS	1800KGS	2200KGS	WEIGHT

單位 : mm

標準配備

- 研磨液供應系統
- 整修齒輪一套
- 上研磨盤安全鎖定

STANDARD ACCESSORIES

- ONE SET OF ABRASIVE SYSTEM
- ONE SET OF DRESSING GEARS
- TOP PLATE SAFETY LOCK

選擇配備

- 厚度自動定寸
- 觸控螢幕控制面板
- 壓力控制

OPTIONS

- D.T.I THICKNESS AUTO CONTROL
- TOUCH PANEL CONTROLLER
- LOAD CELL PRESSURE CONTROL

世極企業有限公司
SECULAR CORPORATION

